Technical Data Sheet

Properties:

AKEMI® Algae and Moss Remover POWER is a rapidly effective, slightly alkaline cleaner based on active chlorine compounds. The product is free of solvents.

Application Area:

AKEMI® Algae and Moss Remover POWER rapidly and thoroughly removes natural layers on facades, roofs, walls and floors made of natural and artificial stone, e.g. marble, granite, concrete ashlar and similar. Organic stains caused by coffee, tea, fruit juice, red wine, cardboard, blossom, bird droppings, tobacco etc. can be excellently removed.

Instructions for Use:

1. Remove deep staining mechanically.
2. a) Bottle/canister: apply undiluted with a brush, sponge, scrubber or spraying device.
   b) Spray bottle: spray evenly from a distance of approx. 25 cm.
3. Allow to work for 10 - 30 minutes. Do not let dry on the surface. Then clean thoroughly with water and a brush.
4. If necessary, repeat cleaning.
5. To prevent regeneration of new green films caused by moss or similar organic layer we recommend to use AKEMI® Algae and Moss Remover LONGLIFE.

Special Notes:

- The product is registered by Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (BAuA) under the no. N-46237 and by Bundesinstitut für Risikobewertung (BfR) under the no. 2054843.
- Wear suitable protection gloves.
- Do not bring into contact with acidic products, release of chlorine possible.
- Do not allow contact with plants, otherwise rinse immediately with water.
- Do not allow contact with metals, wood, clothing or similar in order to avoid discolouring or bleaching.
- Do not refill used material into storing containers.
- Protect from direct sunlight and heat.
- After each use, the spray head of the spray bottle should be removed, cleaned with water and the degassing cap should be reattached.
- Special regulation for Switzerland: AKEMI® Algae and Moss Remover POWER can be used indoors without restriction, outdoors only on facades.
- For proper waste disposal container must be completely emptied.
- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data:

Coverage:	approx. 10 - 20 m²/liter
Colour:	yellowish transparent
Densitiy:	approx. 1.10 g/cm³
pH value:	approx. 11

Storage:

If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 12 months from production.

Health & Safety:

Read Safety Data Sheet before handling or using this product.

AKEMI GmbH · Lechstraße 28 · 90451 Nürnberg · Germany
Tel. +49(0)911-64296-0 · info@akemi.de · www.akemi.com

Technical Data Sheet

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

AKEMI GmbH · Lechstraße 28 · 90451 Nürnberg · Germany
Tel. +49(0)911-64296-0 · info@akemi.de · www.akemi.com