
Technical Data Sheet

Page 1 of 1

Properties:	AKEMI® Car Fresh Up is a silicon-based care product to protect plastics and rubber from weathering and to restore the original appearance of plastics that are already weathered. The product features and benefits are as following: - clear, non-staining spray - easy application - leaves a pleasant smell - removes squeaks and creaks - excellent lubricating and slide properties - protects against humidity and forms a water-repellent layer								
Application Area:	AKEMI® Car Fresh Up is especially developed for numerous applications in car, truck and camper van care and is suited for valeting as well as for maintenance. Typical applications are: - enhancement of colour and finish of plastics, wood or rubber - removes squeaks and creaks in the interior dashboard and seats - suitable for lubricating window channels and sunroof runners, shower cabins, blinds, awning runners, shutters, door hinges, sliding doors, drawer guides etc. - it suits perfectly as a mounting aid for rubbers, hoses and line								
Instructions for use:	1. Shake can well before use. 2. Spray on the surface at a distance from approx. 15 cm or apply with a sprayed cloth. 3. Wipe with a clean, dry cloth and polish.								
Special Notes:	- For professional use only. - For proper waste disposal, the container must be completely emptied. - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.								
Technical Data:	<table><tr><td>Base:</td><td>solution of silicone fluids and synthetic fragrance in hydrocarbon solvents and a butane/propane/isobutane-based propellant</td></tr><tr><td>Odour:</td><td>fruity</td></tr><tr><td>Specific gravity:</td><td>0.788 - 0.808 g/cm³</td></tr><tr><td>Active content:</td><td>5 - 10%</td></tr></table>	Base:	solution of silicone fluids and synthetic fragrance in hydrocarbon solvents and a butane/propane/isobutane-based propellant	Odour:	fruity	Specific gravity:	0.788 - 0.808 g/cm³	Active content:	5 - 10%
Base:	solution of silicone fluids and synthetic fragrance in hydrocarbon solvents and a butane/propane/isobutane-based propellant								
Odour:	fruity								
Specific gravity:	0.788 - 0.808 g/cm³								
Active content:	5 - 10%								
Storage:	If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 24 months from production.								
Health & Safety:	Read Safety Data Sheet before handling or using this product.								
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.								

TDS 11.24