

## Technical Data Sheet

Page 1 of 1

|                              |  |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
|------------------------------|--|-------|-------------|--------|----------------|---------|-------|-------------|------------------|------------------|------------------------|------|-----------------|
| <b>Properties:</b>           | <p>AKEMI® Eco Degreaser is an alcohol-based cleaner for cleaning and degreasing surfaces prior and after to painting.</p> <p>The product is characterized by the following properties:</p> <ul style="list-style-type: none"><li>- excellent cleaning and degreasing properties</li><li>- residue-free evaporation</li><li>- especially formulated for waterborne and special coating</li><li>- antistatic effect</li><li>- also removes tree sap if diluted with 3 parts of water</li><li>- will not damage most plastic or rubber parts</li><li>- will not damage 2-part or chemical cross-linked paint surfaces</li><li>- environmentally friendly, biodegradable</li></ul> |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Application Area:</b>     | <p>An effective, antistatic cleaner for immediate use prior to applying waterborne paint. Due to its antistatic properties the product provides the ideal method for pre-cleansing of plastic prior to painting.</p>   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Instructions for Use:</b> | <ol style="list-style-type: none"><li>1. Apply Eco Degreaser on the surface using a soaked, lint-free cloth or a trigger spray and wipe down the product regularly with a clean, lint-free cloth.</li><li>2. Dry the surface with a further clean, lint-free cloth.</li><li>3. Make sure that the surface is completely clean and dry before painting.</li></ol>   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Special Notes:</b>        | <ul style="list-style-type: none"><li>- For professional use only.</li><li>- If the product is diluted with water, do not allow it to flash off on the surface.</li><li>- For proper waste disposal the container must be completely emptied.</li><li>- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.</li></ul>  |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Technical Data:</b>       | <table><tr><td>Base:</td><td>isopropanol</td></tr><tr><td>Odour:</td><td>mild, pleasant</td></tr><tr><td>Colour:</td><td>clear</td></tr><tr><td>Solubility:</td><td>soluble in water</td></tr><tr><td>Density at 20°C:</td><td>0.79 g/cm<sup>3</sup></td></tr><tr><td>VOC:</td><td>approx. 785 g/l</td></tr></table>   | Base: | isopropanol | Odour: | mild, pleasant | Colour: | clear | Solubility: | soluble in water | Density at 20°C: | 0.79 g/cm <sup>3</sup> | VOC: | approx. 785 g/l |
| Base:                        | isopropanol  |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| Odour:                       | mild, pleasant   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| Colour:                      | clear  |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| Solubility:                  | soluble in water   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| Density at 20°C:             | 0.79 g/cm <sup>3</sup>   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| VOC:                         | approx. 785 g/l  |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Storage:</b>              | <p>If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 24 months from production.</p>   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Health &amp; Safety:</b>  | <p>Read Safety Data Sheet before handling or using this product.</p>   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |
| <b>Important Notice:</b>     | <p>The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.</p>   |       |             |        |                |         |       |             |                  |                  |                        |      |                 |

TDS 01.23