

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **MMA Adhesive 6 min, Part A**

· Article number: 87554A

· UFI: A112-P0DF-400K-C76G

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the mixture

No further relevant information available.

Structural resins

Adhesives

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

· Further information obtainable from:

Laboratory

· 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59

Reachable during the following office hours:

Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS05 GHS07

· Signal word

Danger

· Hazard-determining components of labelling:

methyl methacrylate

methacrylic acid

α,α -dimethylbenzyl hydroperoxide

propylidynetrimehanol, ethoxylated, esters with acrylic acid

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 1)		
· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· Results of PBT and vPvB assessment

· PBT:	Not applicable.
· vPvB:	Not applicable.

· Determination of endocrine-disrupting properties

128-37-0 Butylated hydroxytoluene

List II

SECTION 3: Composition/information on ingredients· **3.2 Mixtures**

· Description: Mixture: consisting of the following components.

· Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5 Reg.nr.: 01-2119463884-26-XXXX	methacrylic acid Acute Tox. 3, H311 Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	<12.5%
	Urethanmethacrylat-Oligomer Skin Irrit. 2, H315; Eye Irrit. 2, H319	<12.5%
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8	α,α -dimethylbenzyl hydroperoxide Org. Perox. E, H242 Acute Tox. 3, H331 STOT RE 2, H373 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Chronic 2, H411 Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C < 10 %	1-5%

(Contd. on page 3)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 2)

CAS: 98-59-9 EINECS: 202-684-8	tosyl chloride Skin Corr. 1B, H314 EUH029	1-5%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46-0000	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-5%
CAS: 28961-43-5 NLP: 500-066-5 Reg.nr.: 01-2119489900-30	propylidynetrimethanol, ethoxylated, esters with acrylic acid Eye Irrit. 2, H319; Skin Sens. 1B, H317 Aquatic Chronic 3, H412	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
- After skin contact: In case of unconsciousness place patient stably in side position for transportation.
- After eye contact: Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.
- After swallowing: Immediately wash with water and soap and rinse thoroughly. Rinse opened eye for several minutes under running water. Then consult a doctor.
- Additional information: Do not induce vomiting; call for medical help immediately. Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Wear fully protective suit.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

(Contd. on page 4)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 3)

- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Prevent seepage into sewage system, workpits and cellars. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- **6.4 Reference to other sections:** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Fumes can combine with air to form an explosive mixture. Use explosion-proof apparatus / fittings and spark-proof tools.
- **7.2 Conditions for safe storage, including any incompatibilities:**
 - **Storage:** Store only in the original receptacle.
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Store away from oxidising agents. Store away from foodstuffs.
 - **Further information about storage conditions:** Protect from exposure to the light. Protect from frost. Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.
 - **Storage class:** 3
 - **7.3 Specific end use(s):** No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

IOELV	Short-term value: 100 ppm Long-term value: 50 ppm
-------	--

DNELs**80-62-6 methyl methacrylate**

Oral	DNEL (Kurzzeit-akut)	0.25 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	1.5 mg/kg bw/day (ARB)
		1.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1.5-13.67 mg/kg bw/day (ARB)

(Contd. on page 5)

EU

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 4)

Inhalative	DNEL (Kurzzeit-akut)	1.5-8.2 mg/kg bw/day (BEV) 29.6-416 mg/m ³ Air (ARB) 6.3-104 mg/m ³ Air (BEV) 208 mg/m ³ Air (ARB) 74.3-104 mg/m ³ Air (BEV)
79-41-4 methacrylic acid		
Dermal	DNEL (Langzeit-wiederholt)	4.25 mg/kg bw/day (ARB) 2.55 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	29.6-88 mg/m ³ Air (ARB) 6.3-6.55 mg/m ³ Air (BEV)
128-37-0 Butylated hydroxytoluene		
Oral	DNEL (Langzeit-wiederholt)	0.25 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (ARB) 5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	3.5 mg/m ³ Air (ARB) 1.74 mg/m ³ Air (BEV)
28961-43-5 propylidynetrimethanol, ethoxylated, esters with acrylic acid		
Oral	DNEL (Langzeit-wiederholt)	1.4 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	10.5 mg/kg bw/day (ARB) 0.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	37 mg/m ³ Air (ARB) 4.9 mg/m ³ Air (BEV)
· PNECs		
80-62-6 methyl methacrylate		
PNEC (wässrig)	10 mg/l (KA) 0.094 mg/l (MW) 0.94 mg/l (SW) 0.15-0.94 mg/l (WAS)	
PNEC (fest)	1.47 mg/kg Trockengew (BO) 0.102 mg/kg Trockengew (MWS) 10.2 mg/kg Trockengew (SWS)	
79-41-4 methacrylic acid		
PNEC (wässrig)	10 mg/l (KA) 0.82 mg/l (MW) 0.82 mg/l (SW)	
PNEC (fest)	1.2 mg/kg Trockengew (BO)	
128-37-0 Butylated hydroxytoluene		
PNEC (wässrig)	0.017 mg/l (KA) 0.00002 mg/l (MW) 0.000199 mg/l (SW) 0.00199 mg/l (WAS)	
PNEC (fest)	0.04769 mg/kg Trockengew (BO) 0.00996 mg/kg Trockengew (MWS) 0.0996 mg/kg Trockengew (SWS)	

(Contd. on page 6)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 5)

28961-43-5 propylidynetrimethanol, ethoxylated, esters with acrylic acid

PNEC (wässrig)	10 mg/l (KA) 0.000195 mg/l (MW) 0.00195 mg/l (SW) 0.0195 mg/l (WAS)
PNEC (fest)	0.00587 mg/kg Trockengew (BO) 0.004 mg/kg Trockengew (MWS) 0.038 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.

· Respiratory protection: Avoid contact with the eyes and skin.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter A/P2

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 6)

- For the permanent contact gloves made of the following materials are suitable:
- As protection from splashes gloves made of the following materials are suitable:
- Not suitable are gloves made of the following materials:
- Eye/face protection

Value for the permeation: Level \leq 480 min

Butyl rubber, BR

Butyl rubber, BR
Nitrile rubber, NBRLeather gloves
Strong material gloves

Tightly sealed goggles

- Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

· <u>General Information</u>	
· <u>Colour:</u>	Black
· <u>Odour:</u>	Specific type
· <u>Odour threshold:</u>	Not determined.
· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Boiling point or initial boiling point and boiling range</u>	>35 °C
· <u>Flammability</u>	Not applicable.
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	1.6 Vol %
· <u>Upper:</u>	12.5 Vol %
· <u>Flash point:</u>	15 °C
· <u>Auto-ignition temperature:</u>	421 °C
· <u>Decomposition temperature:</u>	Not determined.
· <u>pH</u>	Not determined.
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined.
· <u>Dynamic at 20 °C:</u>	130,000-150,000 mPas
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Partition coefficient n-octanol/water (log value)</u>	Not determined.
· <u>Vapour pressure:</u>	Not determined.
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.97 g/cm ³
· <u>Relative density</u>	Not determined.
· <u>Vapour density</u>	Not determined.

9.2 Other information

· <u>Appearance:</u>	
· <u>Form:</u>	Gel
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product does not present an explosion hazard.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	71.5 %
· <u>Solids content:</u>	6.7 %

(Contd. on page 8)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 7)

· <u>Change in condition</u>	Not determined.
· <u>Evaporation rate</u>	
· <u>Information with regard to physical hazard classes</u>	
· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Highly flammable liquid and vapour.
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

· <u>10.1 Reactivity</u>	Stable under recommended transport or storage conditions
· <u>10.2 Chemical stability</u>	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications.
· <u>10.3 Possibility of hazardous reactions</u>	Reacts with strong acids and oxidising agents. Polymerisation.
· <u>10.4 Conditions to avoid</u>	Heat, flames and other sources of ignition
· <u>10.5 Incompatible materials:</u>	strong oxidizing agents Acids bases
· <u>10.6 Hazardous decomposition products:</u>	Carbon monoxide and carbon dioxide Poisonous gases/vapours

SECTION 11: Toxicological information

· <u>11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008</u>	
· <u>Acute toxicity</u>	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:
ATE (Acute Toxicity Estimates)

Oral	LD50	7,216 mg/kg (rat)
Dermal	LD50	4,032-6,757 mg/kg
Inhalative	LC50/4 h	31.6 mg/l (rat)

80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat) (OECD 401)
	NOAEL	2,000 mg/kg (rat)

(Contd. on page 9)

EU

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 8)

Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	4,632 mg/m ³ (rat)
	LC50/4 h	29.8 mg/l (rat)
	NOAEL	25 mg/m ³ (rat)

79-41-4 methacrylic acid

Oral	LD50	1,320 mg/kg (rat)
Dermal	LD50	500-1,000 mg/kg (rabbit)
Inhalative	LC50/4 h	7.1 mg/l (rat)

80-15-9 α,α -dimethylbenzyl hydroperoxide

Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4h	220 mg/m ³ (rat)
	LC50/4 h	1.37 mg/l (rat)
	LC50/48h	17 mg/l (Leuciscus idus) (IUCLID)

98-59-9 tosyl chloride

Oral	LD50	4,680 mg/kg (rat)
------	------	-------------------

128-37-0 Butylated hydroxytoluene

Oral	LD50	>6,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

28961-43-5 propylidynetrimethanol, ethoxylated, esters with acrylic acid

Oral	LD50	2,000 mg/kg (rat)
	NOAEL-Werte	<1,000 mg/kg (rat)
Dermal	LD50	13,200 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Germ cell mutagenicity

Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

Based on available data, the classification criteria are not met.

· Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

SECTION 12: Ecological information**12.1 Toxicity**

· Aquatic toxicity:

80-62-6 methyl methacrylate

EC50/96h	170 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	69 mg/l (daphnia magna) (OECD 202)
EC0	100 mg/l (pseudomonas putida)
NOEC	9.4 mg/kg (Danio rerio.) (OECD 210)
NOEC	>100 mg/l (Selenastrum capricornutum)

(Contd. on page 10)

EU

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 9)

NOELR/72h	>110 mg/l (selenastrum capricornutum) (OECD 201)
NOEC/21d	37 mg/l (daphnia magna) (OECD 211)
EC50/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
LC50/96h	153.9-341.8 mg/l (lem) >79 mg/l (Oncorhynchus mykiss) (OECD 203) 125-275 mg/l (pimephales promelas) 326.4-426.9 mg/l (poecilia reticulata)

79-41-4 methacrylic acid

IC50/72h	0.59 mg/l (Selenastrum capricornutum)
EC10/16h	100 mg/l (microorganisms)
NOELR/72h	8.2 mg/l (Pseudokirchneriella subcapitata)
NOELR/21d	53 mg/l (daphnia magna)
EC50/48h	>130 mg/l (daphnia magna)
EC50/72h	45 mg/l (algae) 20 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	85 mg/l (Oncorhynchus mykiss)

80-15-9 α,α -dimethylbenzyl hydroperoxide

EC50/24h	7 mg/l (daphnia magna) (IUCLID)
EC10/18h	103 mg/l (pseudomonas putida) (IUCLID)
LC50/96h	3.9 mg/l (Oncorhynchus mykiss) (IUCLID)

98-59-9 tosyl chloride

LC50/96h	>100 mg/l (piscis)
----------	--------------------

128-37-0 Butylated hydroxytoluene

IC50/72h	>0.1-1 mg/l (algae)
EC50/48h	0.48 mg/l (daphnia magna)
ErC50/72h	>0.4 mg/l (Desmodesmus subspicatus)
LL0/96h	>0.1-1 mg/l (piscis)
NOEC/21d	0.07 mg/l (daphnia magna)
EC50/72h	0.42 mg/l (Desmodesmus subspicatus) ((EC) Nr. 440/2008, Anhang C.3)
LC50/96h	>0.57 mg/l (Brachydanio rerio) 199 mg/l (piscis)

28961-43-5 propylidynetrimethanol, ethoxylated, esters with acrylic acid

EC50	>1,000 mg/l (BES) (OECD 209)
EC50/48h	70.7 mg/l (daphnia magna) (OECD 202)
EC10	0.323 mg/l (Desmodesmus subspicatus) (OECD 201)
EC50/72h	2.2 mg/l (Desmodesmus subspicatus) (OECD 201)
LC50/96h	1.95 mg/l (Danio rerio.) (OECD 203)

12.2 Persistence and degradability

biodegradable

12.3 Bioaccumulative potential

Does not accumulate in organisms

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 11)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 10)

· 12.7 Other adverse effects**· Additional ecological information:****· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods****· Recommendation:**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:**· Recommendation:**

Disposal must be made according to official regulations.

SECTION 14: Transport information**· 14.1 UN number or ID number****· ADR, IMDG, IATA**

UN2924

· 14.2 UN proper shipping name**· ADR**

2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHACRYLIC ACID, STABILIZED, METHYL METHACRYLATE MONOMER, STABILIZED) FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHACRYLIC ACID, STABILIZED, METHYL METHACRYLATE MONOMER, STABILIZED)

· IMDG, IATA**· 14.3 Transport hazard class(es)****· ADR****· Class**

3 (FC) Flammable liquids.

· Label

3+8

· IMDG**· Class**

3 Flammable liquids.

(Contd. on page 12)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 11)

· <u>Label</u>	3/8
· <u>IATA</u>	
	
· <u>Class</u>	3 Flammable liquids.
· <u>Label</u>	3 (8)
· 14.4 Packing group	II
· ADR, IMDG, IATA	
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	338
· EMS Number:	F-E,S-C
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	1L
· Limited quantities (LQ)	Code: E2
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	1L
· Limited quantities (LQ)	Code: E2
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHACRYLIC ACID, STABILIZED, METHYL METHACRYLATE MONOMER, STABILIZED), 3 (8), II

*** SECTION 15: Regulatory information****· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I

None of the ingredients is listed.

· Seveso category

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements

5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

50,000 t

(Contd. on page 13)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 12)

· REGULATION (EC) No 1907/2006ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU

693.6 g/l

15.2 Chemical safetyassessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS:

Laboratory

· Date of previous version:

19.01.2023

· Version number of previous version:

12

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2

Org. Perox. E: Organic peroxides – Type E/F

(Contd. on page 14)

EU

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.11.2024

Version number 13 (replaces version 12)

Revision: 08.11.2024

Trade name: MMA Adhesive 6 min, Part A

(Contd. of page 13)

Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU