Technical Data Sheet

Properties:

AKEMI® Quartz Intensive Cleaner is an acid-free, ready-to-use cleaner spray made of non-ionic tensides, auxiliary materials, odoriferous substances and solvents. The product is free from phosphates and bases; the tensides contained are biodegradable according to current legislation for surface-active agents. When used properly, surfaces made of quartz which have been treated with AKEMI® Quartz Intensive Cleaner are toxicologically harmless upon contact with food in accordance with DIN 10516 (confirmed by an external German testing institute).

Application Area:

AKEMI® Quartz Intensive Cleaner is suited for a fast and thorough cleaning of kitchen worktops, counter tops and other surfaces made of quartz (such as Caesarstone®, Cambria®, Silestone®, Zodiaq® etc.).

Instructions for Use:

1. Spray AKEMI® Quartz Intensive Cleaner evenly on the surface to be treated.
2. Spread the product with a damp cloth and allow it to work for a short period of time.
3. Afterwards use a damp cloth to remove the dirt. Finish by rubbing the surface with a clean and lint-free cloth until the surface is free of streaks.
4. For stubborn dirt, repeat the procedure again. If necessary, scrub the surface with a brush.

Special Notes:

- Do not apply AKEMI® Quartz Intensive Cleaner on synthetic materials which are not resistant to solvents or rubber. If in doubt, test on an inconspicuous area.
- A surplus of the product causes blooming and spotting. This can be removed with water.
- For proper waste disposal, the container must be completely emptied.
- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data:

Colour:	colourless
Density:	approx. 1.0 g/cm³
pH value:	approx. 10

Storage:

If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 24 months from production.

Health & Safety:

Read Safety Data Sheet before handling or using this product.

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

AKEMI GmbH · Lechstraße 28 · 90451 Nürnberg · Germany
Tel. +49(0)911-64296-0 · Fax +49(0)911-644456 · www.akemi.com