
Technical Data Sheet

Page 1 of 1

Properties: AKEMI® Tyre Dressing is a high-quality formulation that gives the tyre walls a natural new tyre appearance with a single application.

Product features & benefits are as following:

- protects tyre walls from cracking
- resists weathering
- suitable for rejuvenating plastics
- pH-neutral

Application Area: AKEMI® Tyre Dressing is used to enhance the appearance of tyre walls and plastics on the inside and outside of vehicles, e.g.

- tyre walls
- bumpers and trims
- outside mirror housings
- dashboards
- plastic panels

Instructions for use:

1. Wash excessively muddy surfaces prior to application and allow to dry.
2. Shake the spray can well before use.
3. Spray evenly in a thin layer around the tyre walls.

Special Notes:

- For professional use only.
- Do not spray on brake components.
- Not suitable for two-wheelers.
- Avoid use in paintshop areas.
- The spray can should be used at room temperature. Ideal application temperature 10 - 25°C.
- For proper waste disposal, the container must be completely emptied.
- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data:

Basis:	high viscosity silicone oil
Colour:	translucent
Application temperature:	10 - 25°C
Vapour pressure:	3500/20 bar

Storage: If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 5 years from production.

Health & Safety: Read Safety Data Sheet before handling or using this product.

Important Notice: The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 02.24