
Technical Data Sheet

Page 1 of 2

| | |
|------------------------------|---|
| Properties: | AKEMI® Algae and Moss Remover POWER is a rapidly effective, slightly alkaline cleaner based on active chlorine compounds. The product is free of solvents. |
| Application Area: | AKEMI® Algae and Moss Remover POWER rapidly and thoroughly removes natural layers on façades, roofs, walls and floors made of natural and artificial stone, e.g. marble, granite, concrete ashlar and similar. Organic stains caused by coffee, tea, fruit juice, red wine, cardboard, blossom, bird droppings, tobacco etc. can be excellently removed. |
| Instructions for Use: | <ol style="list-style-type: none">1. Remove deep staining mechanically.2.a) Bottle/canister: Apply undiluted with a brush, sponge, scrubber or spraying device.2.b) Spray bottle: Spray evenly from a distance of approx. 25 cm.3. Allow to work for 10 - 30 minutes. Do not let dry on the surface. Then clean thoroughly with water and a brush.4. If necessary repeat cleaning.5. To prevent regeneration of new green films caused by moss or similar organic layer we recommend to use AKEMI® Algae and Moss Remover LONGLIFE. |
| Special Notes: | <ul style="list-style-type: none">- The product is registered by Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (BAuA) under the no. N-46237 and by Bundesinstitut für Risikobewertung (BfR) under the no. 2054843.- Wear suitable protection gloves.- Do not allow contact with plants, otherwise rinse immediately with water.- Do not allow contact with metals, wood, clothing or similar in order to avoid discolouring or bleaching.- Do not refill used material into storing containers.- Protect from direct sunlight and heat.- The spraying head of the spray bottle should be removed and cleaned with water after use.- For proper waste disposal container must be completely emptied. |
| Technical Data: | Coverage: approx. 10 - 20 m ² /liter Colour: yellowish transparent Density: approx. 1.10 g/cm ³ pH value: approx. 11 |
| Storage: | If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 12 months from production. |
| Health & Safety: | Read Safety Data Sheet before handling or using this product. |

TDS 08.20

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.